

XP-002251663

AN - 1998-342483 [30]
AP - JP19960285095 19961028

CPY - KANS-N

DC - P24 Q17

FS - GMPI

IC - A45C11/04 ; B60R7/04

PA - (KANS-N) KANSEI CORP

PN - JP10129356 A 19980519 DW199830 B60R7/04 004pp

PR - JP19960285095 19961028

XIC - A45C-011/04 ; B60R-007/04

XP - N1998-268366

- AB - J10129356 The mount includes a lower case (6) provided with an opening on its upper surface. The spectacles can be placed in and out of the casing through the opening. An upper case (8) is supported to move from rear wall of the lower case through a hinge (7) to open or shut the lower case.
 - A lens pocket (9) that holds both lens of the spectacles is formed to the inner side or bottom of the upper case. The lower case is fixed to the instrument panel of a vehicle through a fixing piece that is provided at the bottom of the lower case.
 - USE - Set in front of e.g. aircraft pilot seat, ship captain seat.
 - ADVANTAGE - Prevents mount from falling off instrument panel. Enables placing spectacles in and out of mount using one hand. Enables insertion of front portion of spectacles in lens pocket without folding sides of spectacles.

- (Dwg.1/6)

IW - SPECTACLE MOUNT INSTALLATION STAND FRONT DRIVE SEAT MOTOR VEHICLE FIX
PIECE BOTTOM LOWER CASE SET LOWER CASE INSTRUMENT PANEL VEHICLE

IKW - SPECTACLE MOUNT INSTALLATION STAND FRONT DRIVE SEAT MOTOR VEHICLE FIX
PIECE BOTTOM LOWER CASE SET LOWER CASE INSTRUMENT PANEL VEHICLE

NC - 001

OPD - 1996-10-28

ORD - 1998-05-19

PAW - (KANS-N) KANSEI CORP

T1 - Spectacles mount installed on stand in front of driver seat in e.g. motor vehicle - has fixing piece provided of bottom of lower case to set lower case on instrument panel of vehicle